ThermaCool® Panel – MATERIAL SAFETY DATA SHEET

1. Chemical Product and Company Identification

Product Name ThermaCool® Wall and Ceiling Panel – TCWP237

Formula n/a

Supplier Datum Phase Change Ltd Telephone +44 (0) 1799 550 222

Email info@datumphasechange.com

2. Composition Information

Patented formulation including natural mined gypsum (Calcium Sulphate Bihydrate – $CaSO_4 2H_20$) with reinforcing glass fibres and incorporating an organic microencapsulated phase change material.

3. Physical Data

Appearance Solid, white colour

Decomposition temperature: CaSO4 + H2O - about 140°C

Flammability Limited flammability Explosion Data Not applicable

4, Health Hazard Data

Main Hazards: Dust formation while drilling or sawing boards by means of electric or hand tools. Dust masks

are recommended.

Other Hazards: None

5. First Aid Measures

Specialised First Aid and Medical Treatment are required for all exposures

General Information: The product is not classified as dangerous. In case of skin irritation, contact a dermatologist.

Eye Contact: No specific measure required. In case of contact with dusts, wash eye with clean water. Seek

medical advice if irritation persists.

Skin: Wash off immediately with soap and water.

Inhalation: Remove person to fresh air. Ensure supply of fresh air.

Most important symptoms and effects, both acute and delayed. – No specific symptoms or effects have been reported. Identification of any immediate medical attention and special treatment needed. – Not applicable. Bring this document if you contact a doctor.

6. Fire Fighting Measures

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Special Hazards arising from The product has limited fire resistance. Packaging may burn.

the Mixture:

Advice for Fire Fighters: Hazardous combustion products may include calcium dioxide and sulphur dioxide.

7. Accidental Release Measures

Personal Precaution, protective equipment and emergency procedures – Avoid contact with eyes and skin. Use protective goggles and gloves. See sections 8 & 9.

Environmental Precautions – Keep out of drains, sewers, ditches and waterways. Minimise use of water to prevent contamination.

8. Handling and Storage

Precautions for Safe Handling: Minimise dust generation while drilling or sawing boards.

Condition for safe storage, Store in a covered, dry, climate controlled area.

including any compatibilities:

Specific End Use: Internal applications only.

9. Exposure Controls, Personal Protection Equipment

Control Parameters: Total inhalable for CaSO4 – TWA: 5mg/m³

Exposure Controls / General protective and Minimise and control dust.

Personal Protection: hygiene measures:

Respiratory protection: If dust cannot be controlled, wear a half face mask conforming to EN 140

Skin protection: Wear gloves to avoid prolonged or repeat contact

Eye protection: Wear safety goggles conforming to EN 166

10. Stability and Reactivity

Reactivity: No materials to avoid known.

Chemical Stability: Keep dry. Stable under normal storage conditions.

Conditions to Avoid: Stable if stored in dry conditions.

Hazardous Decomposition Decomposition takes place from temperatures above 1000°C

Products:

Incompatible Materials None known.

11. Ecological Information

Toxicity: No data available

Persistence and degradability No data available Bio accumulative Potential No data available

Mobility in Soil No data available Results of PBT and vPvB No data available

assessment:

Other Adverse Effects: Product is not allowed to discharge into aquatic environment.

12. Toxicology Information

Information on toxicological effects – No toxicological test has been completed on the product itself.

LD/LD50 Calcium Sulphate, main Acute oral toxicity: LD50 oral rat > 1581 mg/kg – according to guideline OECD 420

component:

Acute inhalation toxicity: LD50 oral rat > 2.61 mg/L – according to guideline OECD 403 Skin irritation: No irritation for rabbit – according to guideline OECD 404

Sensitization: No effect anticipated. Not hazardous by OSHA criteria

13. Disposal Considerations

Waste Treatment Methods: Keep out of drains, ditches and waterways. Wastes from gypsum are normally classified as not

hazardous. Do not co-dispose with municipal waste, but dispose at an authorized site in accordance with local Environmental Regulations. Non-contaminated packaging can be recycled.

14. Transport Information

Not classified as dangerous in terms of transport regulations (IMDG, ADR, RID, IACO/IATA)

NU Number: Not to apply
NU Proper Shipping Name: Not to apply
Transport Hazard Class: Not to apply
Packing Group: Not to apply

Environmental Hazard: Not to apply Special Precaution for Users: Not to apply Transport in Bulk According Not to apply

to Annex II of MARPOL 73/78 and IBC Code:

16. Other information

As the conditions or methods of use are beyond our control, Datum Phase Change Ltd does not assume any responsibility and disclaim any liability for any use of the material. The information and data herein are believed to be accurate and have compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes ass risk of use, storage and handling of the product in compliance with applicable state and local laws and regulations.

Datum Phase Change Ltd makes no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. The implied warranties of merchantability and fitness for a particular purpose are specifically excluded.

The product is manufactured under a quality system certified as conforming with ISO 9001 and complies with EN 15283-2

Abbreviations and Acronyms

TWA: Time Weighted Average **LD50:** Median Lethal Dose

OECD: Organisation for Economic Cooperation and Development

PBT: Persistent, Bio Accumulative, Toxic ChemicalvPvB: very Persistent, very Bio Accumulative chemicalIMDG: International Maritime Dangerous Goods

ADR: Agreement on the transport of Dangerous goods by Road

RID: Regulations on the International transport of Dangerous goods by Rail.

IATA: International Air Transport Association

Datum Phase Change Limited Curles Manor, Pelham Road Clavering Essex. CB11 4PW United Kingdom

Tel: +44 (0) 1799 550222 | Email: info@datumphasechange.com | Web: www.therma.cool